

Our standard package is built around the industry leading Quincy 390 air compressor. Our entire heavy duty compressor package line is made of steel with a powder coated surface. Standard build includes fork lift slots, four point lifting eyes, belt guard, drip pan and Grade D breathing air filtration.

FEATURES

- Kubota D1105 diesel
- Electric start
- Hayes PTO bearing block
- Full instrument panel
- 15 gallon fuel tank
- (2) 60 gallon ASME volume tanks
- Hankison filtration to 0.003 PPM oil vapor
- 4 diver manifold
- Four point lift
- Heavy duty powder coated offshore frame with vibration isolated inner frame
- Upgraded fuel filtration



OPTIONS

- 3 phase electric motor in any voltage or hertz
- Low pressure regulator for downstream pressure
- Pro CO analyzer with LP alarm
- Pro CO analyzer with LP + high temperature alarm
- Low oil shutdown
- High temperature shutdown
- Certified frame
- 250 or 300 psi

SPECIFICATIONS

	Model Q-390DKU
Flow Rate	65 CFM @ 175 psi
Engine/Motor	Kubota Diesel Tier 4 Final
Engine Power	25.8 hp @ 3000 RPM
Max Operating Pressure	200 psi (14 bar)
RPM	877
Number of Stages	2
Lubrication	Pressure Lubrication
Air Quality	Grade D Breathing Air
Dimensions (L x W x H)	96 x 55 x 53 in (244 x 140 x 135 cm)
Weight	2700 lbs (1225 kg)