

FEATURES

- All steel construction with grade 8 steel structural hardware
- 1 to 4 cylinder recharging capable
- Third party tested to meet NFPA 1901 standard
- Ergonomic design for easy operation
- Vertical blast tubes direct air blast and debris away from the operator should a failure occur
- Can be used with existing fill controls
- Designed to fit scuba and SCBA tanks
- Liners reduce wear on cylinders
- Doors open to 60° for easy cylinder insertion

OPTIONS

- Pneumatic doors
- Custom control panel
- Gas analyzer/s
- Storage bank controls
- Nitrox compatible
- High pressure regulator
- Additional gauges
- Multiple fill whip options: SCBA, scuba (DIN or INT [yoke])
- Integrated booster pump
- Oxygen service ready systems



SKU NSS-4 Air / Nitrox
All available options pictured



SCUBA Yoke Whip
SKU NS-WHIP-INT



SKU NCC-2



SKU NCC-2 with fill panel



DIN Whip
SKU NS-WHIP-DIN



SCBA Whip
SKU NS-WHIP-SCBA



SKU NSS-4
Includes 2 fills and 4 charging banks

MODEL	CYLINDERS	PNEUMATIC/MANUAL	DUAL/SINGLE PRESSURE	WEIGHT	DIMENSIONS (L x W x H)
NCC-2	2	Manual	Single	420 lb (190.5 kg)	25 x 26 x 41 in (64 x 66 x 104 cm)
NSS-2	2	Manual or Pneumatic	Single or Dual	560 lb (254 kg)	25 x 26 x 59 in (64 x 66 x 150 cm)
NSS-3	3	Pneumatic	Single or Dual	600 lb (272 kg)	25 x 40 x 59 in (64 x 102 x 150 cm)
NSS-4	4	Pneumatic	Single or Dual	670 lb (474 kg)	25 x 53 x 59 in (64 x 135 x 150 cm)