

FEATURES

- Rigid 2 in sq aluminum frame and belt guard
- ¼ in stainless steel compressor mounting plate
- Vibration mounts below compressor plate & frame
- Two (2) air aftercoolers
- LP air filtration: Norgren Series 74
- Auto drains / DP guages
- Coalescing 1.0 micron
- Oil vapor removal .003 PPM
- Hour meter
- LP dual control head unloaders
- Electric start
- 12 volt battery with box
- 20 amp charging system
- 600 watt inverter

OPTIONS

- 27 Hp Duetz diesel or electric 15 hp 3-phase motor
- One (1) 60-gallon volume tank
- High temperature shutdown or alarm
- Low / High O₂% shutdown or alarm
- CO Analyzer with Alarm and shutdown
- CO₂ Analyzer with Alarm

SPECIFICATIONS*

| | |
|------------------------|-------------------------------------|
| | SKU: 7068 |
| Engine | Honda gas |
| Engine Power | 20 hp (15 kW) |
| Max Operating Pressure | 150 psi |
| Nitrox Produced | 36% at 12 CFM @150 psi (340 L/min) |
| Air Tank | 30 gal steel volume tank |
| Fuel Tank | 6.5 gal |
| Air Quality | Grade D |
| Dimensions (L x W x H) | 56 x 23 x 57 in (135 x 58 x 145 cm) |
| Weight | 624 lbs (283 kg) |

*Specifications are for Honda model. Inquire about diesel or electric.



MEMBRANE SYSTEM

- To (2) Pro O₂ Analyzers, one with Inline sensor
- Membrane rated up to 12 CFM @ 36% O₂
- Auto thermostatic control 110/220 volt heater
- Air intake filter and static mixing tube
- Synthetic food-grade compressor lubricant
- Mix accurate to within 0.1%