

## QUINCY 325 KUBOTA DIESEL

## Industry Leader Quincy 325 Low Pressure Compressor with Loadless Start and Head Unloaders

This package is built with the Kubota 9.4 hp (7 kW) air cooled diesel engine. The package has a 1 gallon surge tank, over pressure relief, drain valve, large air after cooler, check valve, ball valves and plumbing. The frame is made with 6061 aluminum and has an enclosed bottom, lifting eyes, hinged handles and wheels that make it easy to move on and off the job. Perfectly balanced for one man moving; all equipment is inset, compressor and engine have independent vibration absorption mounts and are mounted on an aluminum plate.

## **FEATURES**

- Quincy 325 LP compressor
- Electric start 9.4 hp Kubota diesel engine
- Tach / hour meter
- Aluminum frame with enclosed bottom, lifting eyes, handles and wheels
- Aluminum belt guard
- Over pressure relief valve
- 12 volt sealed battery
- 1.45 gallon fuel tank
- · Air cooled after cooler

## OPTIONS

- Stainless steel package
- Steel frame
- Monitors / alarms for CO, CO<sub>2</sub>, O<sub>2</sub>, H<sub>2</sub>S low pressure and high temp

CDECIFIC ATIONS

- Three-stage breathing air filtration
- 30 gallon volume tank
- Yanmar engine is also available
- 250 or 300 psi



\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \		
SPECIFICATIONS —	SKU: Q-325DK	SKU: Q-325DKL
Flow Rate	19.4 CFM @ 175 psi	19.4 CFM @ 175 psi
Kubota Engine Power	9.4 hp (7 kW)	9.4 hp (7 kW)
Max Operating Pressure	200 psi (14 bar)	200 psi (14 bar)
Number of Stages	2	2
Lubrication	Pressure	Pressure
Air Quality	N/A	Grade D
Dimensions (L x W x H)	48 x 29 x 38 in	48 x 29 x 61 in
	(122 x 74 x 96 cm)	(122 x 74 x 155 cm)
Weight	560 lbs (254 kg)	689 lbs (313 kg)